

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

1 Identification

- **Product identifier**
- **Trade name:** Acrylic Bonding Agent J40
- **Article number:** 83-69081
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106
Tel.: (866) 329-8724
- **Emergency Telephone Number:** Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.
- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol
1,2-benzisothiazol-3(2H)-one
- **Hazard statements**
May cause an allergic skin reaction.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 0
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	0	Fire = 0
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
7732-18-5 water, distilled, conductivity or of similar purity
- **Identification number(s)**
- **EC number:** 231-791-2
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

7664-41-7	ammonia, anhydrous	≤ 1%
4719-04-4	2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	≤ 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7664-41-7 ammonia, anhydrous

PEL	Long-term value: 35 mg/m ³ , 50 ppm
REL	Short-term value: 27 mg/m ³ , 35 ppm Long-term value: 18 mg/m ³ , 25 ppm
TLV	Short-term value: 24 mg/m ³ , 35 ppm Long-term value: 17 mg/m ³ , 25 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 3)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Colorless

· **Odor:** Odorless

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: 0 °C (32 °F)

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17 mm Hg)

· **Density at 20 °C (68 °F):** 1.03573 g/cm³ (8.643 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 4)

- | | |
|---|--|
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| Water: | 98.4 % |
| Solids content: | 25.0 % |
| · Other information | No further relevant information available. |
| · Volatile Organic Compounds: | Contains less than 50 g/L. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect known.
- **on the eye:** No irritating effect known.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

7631-86-9 silicon dioxide, chemically prepared

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 5)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Generally not hazardous for water
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
 It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | Not Regulated |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | Not Regulated |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Not Regulated |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Not Regulated |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 6)

· Transport/Additional information:

· ADR

· U.S. Domestic Ground Shipments: Same as listed for Standard Shipments above.

· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: Same as listed for Standard Shipments above.

· Emergency Response Guide (ERG) Number: Not determine

· UN "Model Regulation": -

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

7664-41-7 ammonia, anhydrous

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

7664-41-7 ammonia, anhydrous

≤1%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/03/2015

Reviewed on 08/03/2015

Trade name: Acrylic Bonding Agent J40

(Contd. of page 7)

· Hazard pictograms



GHS07

· Signal word Warning

· Hazard-determining components of labeling:

2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol

1,2-benzisothiazol-3(2H)-one

· Hazard statements

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

· Date of preparation / last revision 08/03/2015 / 180

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1