



SAFETY DATA SHEET

Revision Date: 07/16/18

1. Identification Of The Substance / Preparation And Of The Company / Undertaking

Product Name: CLARITY Glass Cleaner
Product Number: 891.333
Product Recommended Use: Glass Cleaner
Manufactured For: Winzer Corporation
4060 E. Plano Parkway
Plano, TX 75074
Company Phone: 1-800-527-4126
24 Hour Emergency Phone: INFOTRAC 1-800-535-5053 (US & Canada)

2. Hazards Identification

Classification

Eye Irritation - Category 2B
Gases Under Pressure Liquefied Gas

Signal Word

Warning

Hazardous Statement(s)

Contains gas under pressure; may explode if heated. Causes eye irritation

Pictograms



Precautionary Statement(s)

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Protect from sunlight. Store in a well-ventilated place. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified:

None.

3. Composition / Information On Ingredients



Material	Percent (%)	CAS No.
ETHYLENE GLYCOL MONOBUTYL ETHER	2 - 3	111-76-2
BUTANE	1 - 3	106-97-8
ETHYL ALCOHOL	1 - 2	64-17-5
PROPANE	0 - 2	74-98-6
ISOBUTANE	0 - 2	75-28-5

4. First Aid Measures

Inhalation:

Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

Eye Contact:

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

Skin Contact:

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

Ingestion:

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

5. Fire-Fighting Measures

Suitable Extinguishing Media:

Foam, Alcohol foam, CO₂, Dry Chemical, Water fog.

Unsuitable Extinguishing Media

Water may be ineffective but can be used to cool containers exposed to heat or flame.

Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will not support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes. well-ventilated area. Do not store above 120°F. See product label for additional information.

Fire-Fighting Procedures

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

Special Protective Actions

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

Emergency Procedure:

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Recommended Equipment:

Clean up with an absorbent material and place in closed containers for disposal.

Personal Precautions:

Avoid breathing vapors. Ventilate area. Wear safety glasses and gloves.

Environmental Precautions:

Stop spill/release if it can be done safely.

7. Handling And Storage

General:

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

Ventilation Requirements:

Use in a well ventilated place.

Storage Room Requirements:

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

8. Exposure Controls / Personal Protection

Eye Protection:

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

Skin Protection:

Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory Protection:

In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
BUTANE								800	1900			
ETHYL ALCOHOL	1000	1900			1			1000	1900			
ETHYLENE GLYCOL MONOBUTYL ETHER	50	240			1		1	5	24			
ISOBUTANE								800	1900			
PROPANE	1000	1800			1			1000	1800			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BUTANE	1000			
ETHYL ALCOHOL			1000	
ETHYLENE GLYCOL MONOBUTYL ETHER	20	97		
ISOBUTANE	1000			
PROPANE	See Appendix F: Minimal Oxygen Content			

(C) - Ceiling limit

9. Physical And Chemical Properties

Appearance:	N/A	Vapor Pressure (Mm Hg):	N/A
Odor:	N/A	Vapor Density (Air=1):	Slower than ether
Odor Threshold:	N/A	Evaporation Rate:	Slower than ether
Boiling Point:	N/A	Density:	7.95700 lb/gal
Freezing Point:	N/A	Density VOC:	0.79529 lb/gal
Flammability:	Flash point at or above 200°F/93°C	Solubility In Water:	N/A
Flash Point:	N/A	Partition Coefficient:	N/A
Autoignition Temperature:	N/A	(KOW):	N/A
Lower Explosion Level:	N/A	Volatility Including Water (%):	N/A
Upper Explosion Level:	N/A	Volatile Organic Compounds (Voc):	9.99485%
		Dielectric Strength (Volts):	N/A
		Decomposition Temperature:	N/A
		Viscosity:	N/A

10. Stability And Reactivity

Stability:

The product is stable under normal storage conditions.

Conditions to Avoid:

High temperatures.

Incompatible Materials:

None known.

Hazardous Reactions/Polymerization:

None known.

Hazardous Decomposition Products:

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

11. Toxicological Information**Skin Corrosion/Irritation:**

No data available

Classification of the Substance or Mixture:

There is no toxicological data available for this product.

Serious Eye Damage/Irritation:

Causes eye irritation

Carcinogenicity:

No data available

Germ Cell Mutagenicity:

No data available

Reproductive Toxicity:

No data available

Respiratory/Skin Sensitization:

No data available

Specific Target Organ Toxicity - Single Exposure:

No data available

Specific Target Organ Toxicity - Repeated Exposure:

No data available

Aspiration Hazard:

No data available

Acute Toxicity:

No data available

Potential Health Effects - Miscellaneous:

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can be absorbed through the skin in harmful amounts. May cause injury to the kidneys, liver, blood and/or bone marrow. Repeated overexposure may result in damage to the blood. Eye contact may cause corneal injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother

0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m3 (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

LC50 (female rat): 450 ppm (4-hour exposure) (2)

LC50 (male rat): 486 ppm (4-hour exposure) (2)

LD50 (oral, male weanling rat): 3000 mg/kg (1)

LD50 (oral, 6-week old male rat): 2400 mg/kg (1)

LD50 (oral, yearling male rat): 560 mg/kg (1)

LD50 (oral, female rat): 530 mg/kg; 2500 mg/kg (1) LD50 (oral, male mouse): 1230 mg/kg (1)

LD50 (oral, rabbit): 320 mg/kg (1)

LD50 (dermal, male rabbit): 406 mg/kg (cited as 0.45 mL/kg) (1)

0000075-28-5 ISOBUTANE

LC50 (mouse, inhalation): 520,000 ppm (52%); 2-hour exposure.(4)

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m³) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)LC50 (rat): 276000 ppm (658000 mg/m³) (4-hour exposure); cited as 658 mg/L (4- hour exposure) (9)**12. Ecological Information****Toxicity:**

No data available.

Classification of the substance or mixture

There is no ecological data available for this product.

Persistence and Degradability:

No data available.

Bio-Accumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

13. Disposal Considerations**Water Disposal:**

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

14. Transport Information**U.S. DOT Information:**

PROPER SHIPPING NAME: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

IMDG Information:

PROPER SHIPPING NAME: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)
 HAZARD CLASS/DIVISION: 2.2
 UN/NA NUMBER: UN1950

IATA Information:

PROPER SHIPPING NAME: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)
 HAZARD CLASS/DIVISION: 2.2
 UN/NA NUMBER: UN1950

15. Regulatory Information


CAS No.	Chemical Name	Percent (%)	Regulation List
111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	2 - 3	SARA313, CERCLA, SARA312, VOC, TSCA, ACGIH, OSHA
106-97-8	BUTANE	1 - 3	SARA312, VOC, TSCA, ACGIH
64-17-5	ETHYL ALCOHOL	1 - 2	SARA312, VOC, TSCA, ACGIH, OSHA
74-98-6	PROPANE	0 - 2	SARA312, VOC, TSCA, ACGIH, OSHA
75-28-5	ISOBUTANE	0 - 2	SARA312, VOC, TSCA, ACGIH

16. Other Information**Glossary**

* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS. ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESLEffects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 1
FLAMMABILITY	1
Physical Hazard	0
Personal Protection	A

NFPA**DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks