



Revision Number: 002.1

Issue date: 11/11/2011

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** DELETE \*PR 50 DR QB300 ADH SO **IDH number:** 827630  
**Product type:** Solvent based adhesive **Region:** United States  
**Company address:** **Contact information:**  
 Henkel Corporation Telephone: 800.624.7767  
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center  
 Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC  
 1-800-424-9300 (toll free) or 1-703-527-3887

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

<b>Physical state:</b>	pasty	<b>HMIS:</b>	
<b>Color:</b>	beige	<b>HEALTH:</b>	2
<b>Odor:</b>	slightly, mineral-oil-like	<b>FLAMMABILITY:</b>	3
		<b>PHYSICAL HAZARD:</b>	0
		<b>Personal Protection:</b>	See MSDS Section 8

**DANGER:** EXTREMELY FLAMMABLE LIQUID AND VAPOR.  
 VAPOR MAY CAUSE FLASH FIRE.  
 HARMFUL IF SWALLOWED OR INHALED.  
 MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

**Relevant routes of exposure:** Inhalation, Skin contact

**Potential Health Effects**

**Inhalation:** Irritates the nose, throat and respiratory system. Exposure to high doses may cause central nervous system depression. Such doses may also cause adverse effects in the liver, kidneys, and lungs. Overexposure to hexane may result in peripheral and central nervous system damage, which may be permanent. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Skin contact:** Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

**Eye contact:** Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Ingestion:** Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Existing conditions aggravated by exposure:** Eye, skin and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Limestone	1317-65-3	30 - 60
Hydrocarbon aliphatic C4-11 < 0,1% benzene	64742-49-0	10 - 30
Kaolin	1332-58-7	5 - 10
n-Hexane	110-54-3	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - 1

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
<b>Skin contact:</b>	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If skin irritation persists, call a physician.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting, seek medical advice immediately. Never give anything by mouth to an unconscious person.

### 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	-17.80 °C (0.04 °F) Supplier's method
<b>Autoignition temperature:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	1 %
<b>Flammable/Explosive limits - upper:</b>	7 %
<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray.
<b>Special firefighting procedures:</b>	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing.
<b>Unusual fire or explosion hazards:</b>	Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along floor to an ignition source.
<b>Hazardous combustion products:</b>	Carbon dioxide. Carbon monoxide.

### 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

<b>Environmental precautions:</b>	Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Ventilate area.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear suitable protective clothing, gloves and eye/face protection.

## 7. HANDLING AND STORAGE

**Handling:** During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Do not cut, grind, weld, or drill on or near this container. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8. Do not taste or swallow. Keep out of the reach of children.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Hydrocarbon aliphatic C4-11 < 0,1% benzene	None	None	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
n-Hexane	(SKIN) 50 ppm TWA	500 ppm (1,800 mg/m3) TWA	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Quartz (SiO <sub>2</sub> )	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:** Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** pasty  
**Color:** beige  
**Odor:** slightly, mineral-oil-like  
**Odor threshold:** Not available.  
**pH:** not applicable  
**Vapor pressure:** 155 mm hg (20 °C (68°F))  
**Boiling point/range:** 57 - 74 °C (134.6 - 165.2 °F) Supplier's method  
**Melting point/ range:** Not available.  
**Specific gravity:** 1.369  
**Vapor density:** Heavier than air.  
**Flash point:** -17.80 °C (0.04 °F) Supplier's method

**Flammable/Explosive limits - lower:** 1 %  
**Flammable/Explosive limits - upper:** 7 %  
**Autoignition temperature:** Not available.  
**Evaporation rate:** 4.4 Greater than butyl acetate., (Butyl acetate = 1)  
**Solubility in water:** Insoluble  
**Partition coefficient (n-octanol/water):** Not available.  
**VOC content:** 20 %; 280 g/l (calculated)  
**Viscosity:** 280,000 - 400,000 mPa.s

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of storage and use.  
**Hazardous reactions:** Will not occur.  
**Hazardous decomposition products:** Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.  
**Incompatible materials:** Strong oxidizing agents.  
**Conditions to avoid:** Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Hydrocarbon aliphatic C4-11 < 0,1% benzene	No	No	No
Kaolin	No	No	No
n-Hexane	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO <sub>2</sub> )	Known To Be Human Carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs
Limestone	Nuisance dust
Hydrocarbon aliphatic C4-11 < 0,1% benzene	Central nervous system, Irritant, Kidney, Lung
Kaolin	Nuisance dust
n-Hexane	Developmental, Irritant, Lung, Nervous System, Reproductive
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity
Quartz (SiO <sub>2</sub> )	Immune system, Lung, Some evidence of carcinogenicity

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

<b>Recommended method of disposal:</b>	Dispose of according to Federal, State and local governmental regulations.
<b>Hazardous waste number:</b>	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

#### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Adhesives
<b>Hazard class or division:</b>	3
<b>Identification number:</b>	UN 1133
<b>Packing group:</b>	II

#### International Air Transportation (ICAO/IATA)

<b>Proper shipping name:</b>	Adhesives
<b>Hazard class or division:</b>	3
<b>Identification number:</b>	UN 1133
<b>Packing group:</b>	II

#### Water Transportation (IMO/IMDG)

<b>Proper shipping name:</b>	ADHESIVES
<b>Hazard class or division:</b>	3
<b>Identification number:</b>	UN 1133
<b>Packing group:</b>	II

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
<b>TSCA 12(b) Export Notification:</b>	None above reporting de minimus
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimus
<b>CERCLA/SARA Section 311/312:</b>	Immediate Health, Delayed Health, Fire
<b>CERCLA/SARA 313:</b>	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). n-Hexane (CAS# 110-54-3).
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

<b>CEPA DSL/NDSL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.