

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET  
(AP1 - Aerosol Product)

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURED BY:  
Custom-Pak Products Inc.  
Germantown, WI 53022

FORMULA # 18E049N12  
Company Phone Number: (262) 251-6180  
24 Hour Emergency: (800) 688-4005  
Foreign Emergency: (01)(262) 236-8130 [USA]

DATE PRINTED: 06/01/06  
LAST REVISION: 04/30/03

PACKAGED FOR: (C1133)  
SHEBOYGAN PAINT COMPANY  
SHEBOYGAN, WI 53081

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

#	COMPONENT	CAS#	% by WT.	SARA 313 LISTED CARCINOGEN BY:		
				LISTED	NTP	IARC OSHA
1	LT ALIPHATIC NAPHTHA	8032-32-4	15-21	N	N	N
2	PROPANE	74-98-6	15-21	N	N	N
3	ACETONE	67-64-1	15-21	N	N	N
4	HEPTANE	142-82-5	15-21	N	N	N
5	N-BUTANE	106-97-8	5-8	N	N	N

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: DANGER! Extremely Flammable. Contents Under Pressure.

APPEARANCE/ODOR: Liquid Spray Mist / Solvent Odor

POTENTIAL HEALTH EFFECTS: See Section 11 for more information.

LIKELY ROUTES OF EXPOSURE: Eye contact, skin contact, ingestion, and inhalation

EYE: Contact may cause redness, irritation, tearing, and blurred vision

SKIN: Contact may dry skin causing cracks and irritation

INGESTION: May be harmful if swallowed

INHALATION: Exposure to high concentrations of vapors may cause drowsiness, breathing difficulty, respiratory irritation, or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET  
(AP1 - Aerosol Product)

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:  
Asthma and other respiratory ailments.  
TARGET ORGANS: Kidney Liver Lung Brain

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### SECTION 4: FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. If irritation develops get medical attention.  
SKIN CONTACT: Remove contaminated clothing and wash before reuse. Wash skin with soap and water. Get medical attention if irritation develops.  
INHALATION: Move to fresh air. Contact emergency medical support if breathing stops or is irregular.  
INGESTION: Do NOT induce vomiting. Get medical attention immediately.

#### SECTION 5: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: CO2 (Carbon Dioxide), dry chemical, or water fog.  
UNSUITABLE EXTINGUISHING MEDIA: Water spray may be unsuitable. However, if water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.  
PRODUCTS OF COMBUSTION: These products are carbon oxides (CO,CO2).  
PROTECTION OF FIREFIGHTERS: Full protective equipment including self-contained breathing apparatus should be used.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protection recommended in Section 8.  
ENVIRONMENTAL PRECAUTIONS: None known.

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET

(AP1 - Aerosol Product)

METHODS OF CONTAINMENT: Absorb spilled liquid in suitable material.  
METHODS OF CLEAN-UP: Use spark-proof tools to sweep or scrape up and containerize.  
OTHER INFORMATION: Ventilate the area.

SECTION 7: HANDLING AND STORAGE

HANDLING:

Vapors may ignite explosively. Prevent buildup of vapors; use with adequate ventilation. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate (burn) container.

STORAGE:

Store in dry well ventilated areas. Do not expose to heat or store at temperatures above 48 degrees C (120 degrees F).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

#	COMPONENT	ACGIH TLV-STEL	ACGIH TLV-TWA	OSHA PEL-TWA
1	LT ALIPHATIC NAPHTHA	N/E	N/E	N/E
2	PROPANE	1800 ppm	2500 ppm	1000 ppm
3	ACETONE	750 ppm	500 ppm	1000 ppm
4	HEPTANE	500 ppm	400 ppm	500 ppm
5	N-BUTANE	N/E	800 ppm	800 ppm

ENGINEERING CONTROLS: Not generally required if product is applied in small quantities. If product is applied in larger quantities, provide ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

EYE/FACE PROTECTION: Wear safety glasses with side shields. Have eye wash facilities immediately available.

SKIN PROTECTION: Chemical resistant gloves if contact is likely.

RESPIRATORY PROTECTION: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

GENERAL HYGIENE CONSIDERATIONS: Wash thoroughly after handling.

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET  
(AP1 - Aerosol Product)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: see product description  
Odor: Solvent Odor  
Physical State: Aerosol - Pressurized Liquid  
Freezing Point: Not Established (mixture)  
Boiling Range: <-18 C to 177 C (<0 F to 350 F)  
Flash Point: <-18 C (<0 F)  
Evaporation Rate: Faster than ether  
Upper Flammability Limit: Not Established (mixture)  
Lower Flammability Limit: Not Established (mixture)  
Vapor Pressure: Approximately 50 psig @ 10 C (70 F)  
Specific Gravity: 0.824 @15 C (60 F)  
Solubility (water): Negligible  
Percent Volatile, wt. %: 72.4  
VOC Percent (CA): 57.4  
MIR Number (CA): 0.495  
Coating Category (CA): EXACT MATCH FINISH: INDUSTRIAL

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET  
(AP1 - Aerosol Product)

SECTION 11: TOXICOLOGICAL INFORMATION

#	COMPONENT	LD50 Oral	LD50 Dermal
1	LT ALIPHATIC NAPHTHA	N/E	N/E
2	PROPANE	1000 mg/kg	1800 mg/kg
3	ACETONE	1000 mg/kg	2400 mg/kg
4	HEPTANE	N/E	N/E
5	N-BUTANE	N/E	N/E

See section 3 for other acute effect information.

CHRONIC EFFECTS: Prolonged over-exposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated the repeated and prolonged occupational OVER-EXPOSURE to solvents with brain and nervous system damage. The deliberate misuse by concentrating and inhaling the vapors may be harmful or fatal.

CARCINOGENICITY: See Section 2 for additional information.

SECTION 12: ECOLOGICAL INFORMATION

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Do not puncture, incinerate or place container in trash compactor. Dispose of product in accordance with Federal, State, and Local regulations. Empty containers are 95% steel; recycle where allowed.

Product Description:  
GEHL  
GRAY ENAMEL  
PART NO. 902876

MATERIAL SAFETY DATA SHEET  
(AP1 - Aerosol Product)

SECTION 14: TRANSPORTATION INFORMATION

US DOT (Ground)  
Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D

US DOT (Air)  
Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D-AIR

IATA (Domestic Air)  
CONSUMER COMMODITY, ID 8000, CLASS 9, MISCELLANEOUS LABEL, Packing Instruction: 910.

IATA (International Air)  
Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.; Class: 2.1; UN1950; Packing  
Instruction: Y203; Authorization: LTD. QTY.; FLAMMABLE GAS label required on box.

IMDG (Water)  
Proper Shipping Name: AEROSOL PRODUCT, LTD QTY, IMDG Class 2, Page 2102, UN1950,  
Packing Group II, Marine Pollutant: Yes.

SECTION 15: REGULATORY INFORMATION

International Chemical Inventory  
TSCA: United States The components of this product are listed on the TSCA inventory.  
DSL/NDSL: Canada The components of this product are listed on the DSL inventory.  
AICS: Australia The components of this product are listed on the AICS inventory.

Section 313 Toxic Chemicals

See section 2. Chemicals marked with a "Y" are subject to the  
SARA reporting requirements under 40 cfr 372.45(c)(5).

SECTION 16: OTHER INFORMATION

HMIS: Hazardous Material Identification System

Health - 2 Fire - 4 Reactivity - 1

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard,  
4 = extreme hazard

This MSDS is based on information believed to be reliable and accurate. Because of  
changing reporting requirements and other variables it is impossible to guarantee  
the accuracy of the information contained in this document. It is the responsi-  
bility of the user to determine proper personal protection based on the actual  
condition of use and to comply with all Federal, State and Local laws and regulations.