

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 765-1826 NAPA HEAVY DUTY HEADLINER & CARPET ADHESIVE 16.75 OZ (PTX27828)
Item No: 21230
Product Type: Aerosol adhesive

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
N-HEXANE 110-54-3	20-30	50 ppm	500 ppm; 1800 mg/m ³
PETROLEUM GASES, LIQUIFIED 68476-85-7	20-30	1000 ppm; 1800 mg/m ³ TWA ACGIH	Not listed
ACETONE 67-64-1	10-30	500 ppm	1000 ppm; 2400 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: Harmful if inhaled. Deliberately concentrating and inhaling the vapor may be harmful or fatal. Aspiration hazard if swallowed. May cause eye, skin and respiratory irritation. Prolonged and repeated exposure to methyl ethyl ketone and/or n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of arms and legs) and result in muscular weakness and loss of sensation.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
ACETONE 67-64-1	10-30		A4 - Not Classifiable as a Human Carcinogen	

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Extremely flammable aerosol per flame projection test

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Oxides of carbon

Unusual Fire/Explosion Hazards: Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).
Handling: Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Avoid contact with skin and eyes. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber liquid
Odor: Solvent
Boiling Point: >100°F
pH: N/AP
Solubility in Water: Insoluble
Specific Gravity: 0.7
VOC(Wt.%): 64%
Vapor Pressure: n/d
Vapor Density (Air=1): >1
Evaporation Rate: >1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers, Acids, Amines, Sulfuric acid
Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking
Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.
US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
U.S. Department of Transportation - DOT - 49 CFR (Ground)
DOT Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.1

Product Name: 765-1826 NAPA HEAVY DUTY HEADLINER &
CARPET ADHESIVE 16.75 OZ (PTX27828)

Item No. 21230

14. TRANSPORTATION INFORMATION

UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity

Hazard Class: Class 2.1

UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

HEXANE

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: February 14, 2013
Revision Number: 1