

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

1 Identification

- **Product identifier**
- **Trade name:** Touch 'n Foam Max Fill
- **Product code:** EHS 9803
- **Recommended use and restriction on use**
- **Recommended use:** Sealant
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Convenience Products, Foam Products Division
866 Horan Drive
Fenton, MO 63026-2614
Phone: 636-349-5855
Toll-Free: 1-800-325-6180
- **Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585



2 Hazard(s) identification

- **Classification of the substance or mixture**
- Flam. Aerosol 1 H222 Extremely flammable aerosol.
- Press. Gas H280 Contains gas under pressure; may explode if heated.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Lact. H362 May cause harm to breast-fed children.
- STOT SE 3 H335 May cause respiratory irritation.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS02 GHS04 GHS07 GHS08

· Signal word: Danger

· Hazard-determining components of labeling:

diphenylmethanediisocyanate, isomers and homologues
tris(2-chloroisopropyl)-phosphate
alkenes, C12-24, chloro
4,4'-methylenediphenyl diisocyanate

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 1)

· **Hazard statements:**

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H362 May cause harm to breast-fed children.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements:**

- P201 Obtain special instructions before use.
- P263 Avoid contact during pregnancy/while nursing.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P260 Do not breathe mist/vapors/spray.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P211 Do not spray on an open flame or other ignition source.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves and eye protection.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

- There are no other hazards not otherwise classified that have been identified.
- 0 % of the mixture consists of component(s) of unknown toxicity.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

9016-87-9	diphenylmethanediisocyanate, isomers and homologues  Resp. Sens. 1, H334; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-40%
101-68-8	4,4'-methylenediphenyl diisocyanate  Resp. Sens. 1, H334; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-20%
115-10-6	dimethyl ether  Flam. Gas 1, H220  Press. Gas, H280	5-<10%
693217-63-9	Soybean oil, reaction products with ethaneperoxoic acid Eye Irrit. 2B, H320	5-<10%
75-28-5	isobutane  Flam. Gas 1, H220  Press. Gas, H280	5-<10%
13674-84-5	tris(2-chlorisopropyl)-phosphate  Acute Tox. 4, H302	2.5-5%
74-98-6	propane  Flam. Gas 1, H220  Press. Gas, H280	2.5-5%

· Additional information:

For the wording of the listed Hazard Statements refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 3)

- **After eye contact:**
Immediately remove contact lenses if possible.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:**
Asthma attacks
Headache
Breathing difficulty
Allergic reactions
Coughing
Nausea
Gastric or intestinal disorders when ingested.
Irritant to skin and mucous membranes.
Irritant to eyes.
Dizziness
Disorientation
- **Danger:**
Danger of impaired breathing.
Danger of disturbed cardiac rhythm.
Danger of pulmonary edema.
Danger of pneumonia.
Danger of convulsion.
- **Indication of any immediate medical attention and special treatment needed:**
Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
Treat skin and mucous membrane with antihistamine and corticoid preparations.
In cases of irritation to the lungs, initial treatment with corticoid steroid inhalants.
Monitor circulation.
If necessary oxygen respiration treatment.
Medical supervision for at least 48 hours.
Contains isocyanates. May produce an allergic reaction.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Water in flooding quantities.
- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**
Danger of receptacles bursting because of high vapor pressure if heated.
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 4)

· **Additional information:**

- Eliminate all ignition sources if safe to do so.
- Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- Cool endangered receptacles with water spray.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures:**

- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation.
- Keep away from ignition sources.
- Protect from heat.
- Isolate area and prevent access.
- Keep people at a distance and stay upwind.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

- Allow to solidify. Pick up mechanically.
- Send for recovery or disposal in suitable receptacles.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

· **Reference to other sections:**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

- Keep away from heat and direct sunlight.
- Use only in well ventilated areas.

· **Information about protection against explosions and fires:**

- Keep ignition sources away - Do not smoke.
- Keep respiratory protective device available.
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material.
- Emergency cooling must be available in case of nearby fire.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

- Store in a cool location.
- Observe official regulations on storing packagings with pressurized containers.
- Provide ventilation for receptacles.
- Avoid storage near extreme heat, ignition sources or open flame.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 5)

- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Specific end use(s):** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL (USA)	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV (USA)	Long-term value: 0.051 mg/m ³ , 0.005 ppm
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm
LMPE (Mexico)	Long-term value: 0.005 ppm

115-10-6 dimethyl ether

WEEL (USA)	Long-term value: 1000 ppm
EL (Canada)	Long-term value: 1000 ppm

75-28-5 isobutane

TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm
EV (Canada)	Long-term value: 800 ppm
LMPE (Mexico)	Long-term value: 1000 ppm

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs and BEIs book
EL (Canada)	Long-term value: 1000 ppm
EV (Canada)	Long-term value: 1000 ppm
LMPE (Mexico)	Long-term value: 1000 ppm

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 6)

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Clean skin thoroughly immediately after handling the product.

· **Engineering controls:** No relevant information available.

· **Breathing equipment:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures**

See Section 7 for additional information.

No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

Form:	Aerosol
Color:	Amber colored
Odor:	Light Petroleum-like

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 7)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	-42 °C (-44 °F) (propellant)
· Flash point:	-104 °C (-155 °F) (propellant)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.01 g/cm ³ (8.428 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not determined.
· Evaporation rate:	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity Dynamic:	Not determined.
Kinematic:	Not determined.
VOC (California):	172.4 g/L (EPA Method 24)
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions:**
Develops readily flammable gases / fumes.
Flammable.
Reacts with oxidizing agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Danger of receptacles bursting because of high vapor pressure if heated.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 8)

Contact with acids releases toxic gases.
Toxic fumes may be released if heated above the decomposition point.

· **Conditions to avoid:**

Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.

· **Incompatible materials:** No relevant information available.

· **Hazardous decomposition products:**

Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Hydrogen cyanide (prussic acid)
Phosphorus oxides (e.g. P₂O₅)
Chlorine

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

· **Primary irritant effect:**

· **On the skin:** Irritant to skin and mucous membranes.

· **On the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through inhalation.
Sensitization possible through skin contact.

· **Subacute to chronic toxicity:**

Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· **IARC (International Agency for Research on Cancer):**

9016-87-9	diphenylmethanediisocyanate, isomers and homologues
-----------	---

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

· **Acute effects (acute toxicity, irritation and corrosivity):** Vapors have narcotic effect.

· **Repeated dose toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Lact.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 9)

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** May cause respiratory irritation.
- **STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols |
| · ADR | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| · IMDG | AEROSOLS, MARINE POLLUTANT |

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 10)

· IATA

AEROSOLS, flammable

· Transport hazard class(es)

· DOT



· Class

2.1

· Label

2.1

· ADR



· Class

2 5F Gases

· Label

2.1

· IMDG



· Class

2.1

· Label

2.1

· IATA



· Class

2.1

· Label

2.1

· Packing group

This UN-number is not assigned a packing group.
Aerosols are not assigned a packing group.

· Environmental hazards

· Marine pollutant:

Symbol (fish and tree)
(alkenes, C12-24, chloro)

· Special precautions for user

Warning: Gases

· Danger code (Kemler):

-

· EMS Number:

F-D,S-U

· Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code

Not applicable.

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 11)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency):

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

CBD

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· IARC (International Agency for Research on Cancer):

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

3

101-68-8 4,4'-methylenediphenyl diisocyanate

3

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canada

· Canadian substance listings

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%):

101-68-8 4,4'-methylenediphenyl diisocyanate

· Canadian Ingredient Disclosure list (limit 1%):

8001-79-4 Castor oil

(Cont'd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/18/2016

Revision: 03/18/2016

Trade name: Touch 'n Foam Max Fill

(Cont'd. of page 12)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 03/18/2016 / -**Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Lact.: Reproductive toxicity, Additional category, Effects on or via lactation
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com