

Safety Data Sheet
ULTRALITE S2 GRAY

Safety Data Sheet dated: 06/16/2021 - version 4

Date of first edition: 05/26/2015



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: ULTRALITE S2 GRAY

Trade code: 9012015

Recommended use of the chemical and restrictions on use

Recommended use: Cement based levelling mortar

Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive

33442 - Deerfield Beach - FL - USA

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Skin Corr. 1A	Causes severe skin burns and eye damage.
Eye Dam. 1	Causes serious eye damage.
Skin Sens. 1	May cause an allergic skin reaction.
Carc. 1A	May cause cancer if inhaled.
STOT SE 3	May cause respiratory irritation.
STOT RE 1	Causes damage to organs through prolonged or repeated exposure if inhaled.

Label elements

Pictograms and Signal Words



Danger

Hazard statements:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a doctor.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
25-50 %	PORTLAND CEMENT	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314	
25-50 %	Silica Sand	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	
1-2.5 %	CALCIUM FORMATE	CAS:544-17-2	Eye Dam. 1, H318; Comb. Dust, USH003	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:
(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: N.A.
- Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

- Take up mechanically and dispose of according to local/state/federal regulations
 - Scoop into containers and seal for disposal.
 - Retain contaminated washing water and dispose it.
-

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Do not use on extensive surface areas in premises where there are occupants.
- Use localized ventilation system.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

- Storage temperature: N.A.
- Always keep in a well ventilated place.
- Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour Note
PORTLAND CEMENT	OSHA			15				
	OSHA			5				
	ACGIH			1				A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
	ACGIH			1				A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma
	MAK	AUSTRIA		5				
Silica Sand	MAK	SWITZERLAND		5				
	ACGIH			0,025				A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: powder Grey

Odour: cement like

Odour threshold: No data available

pH: No data available

pH (water dispersion, 10%): 12.00

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: Not Applicable

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: No data available

Relative density: 1.10 g/cm³

Solubility in water: dispersible

Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available

Oxidizing properties: No data available

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
Silica Sand	CAS: 14808-60-7	a) Aquatic acute toxicity : LC50 carp > 10000,00000 mg/L 72h
CALCIUM FORMATE	CAS: 544-17-2	a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio >= 1000 mg/L 96h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

ADR-UN number: N.A.

DOT-UN Number: N.A.

IATA-Un number: N.A.

IMDG-Un number: N.A.

UN proper shipping name

ADR-Shipping Name: N.A.

DOT-Proper Shipping Name: N.A.

IATA-Technical name: N.A.

IMDG-Technical name: N.A.

Transport hazard class(es)

ADR-Class: N.A.

DOT-Hazard Class: N.A.

IATA-Class: N.A.

IMDG-Class: N.A.

Packing group

ADR-Packing Group: N.A.

DOT-Packing group: N.A.

IATA-Packing group: N.A.
IMDG-Packing group: N.A.

Environmental hazards

Marine pollutant: No
Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

N.A.

Road and Rail (ADR-RID) :

N.A.

Air (IATA) :

N.A.

Sea (IMDG) :

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

PORTLAND CEMENT	is listed in TSCA	Section 8b
Silica Sand	is listed in TSCA	Section 8b
CALCIUM FORMATE	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand	Listed as carcinogen
-------------	----------------------

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

PORTLAND CEMENT

Silica Sand

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

PORTLAND CEMENT

Silica Sand

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

PORTLAND CEMENT

Silica Sand

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

No substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 6/16/2021 - version 4

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 0 = Not Combustible

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer.
H350	May cause cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
USH003	May form combustible dust concentrations in air.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 16. OTHER INFORMATION