


| | | |
|--|--|---------------------------|
|  | | Page: 1 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 1/4/2018 |
| | | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid | | Version: 1.3 |
| 773636 | | |

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ DEX/MERC Automatic Transmission Fluid

| | |
|---|---|
| Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL | Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL |
|---|---|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|--|------------|---|-------------------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | Asp. Tox. 1; H304 | 11.8259 |
| MINERAL OIL | | This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom) | 5.0063 |




| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 05/22/2017 |
| | Print Date: 1/4/2018 |
| | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid 773636 | Version: 1.3 |

| | | | |
|---------------------------------------|--|--|--------|
| | | (2012). | |
| METHACRYLATE COPOLYMER | | Eye Irrit. 2A; H319 | 1.6604 |
| ALKOXYLATED LONG-CHAIN ALKYL AMINE | | Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 3; H402 Aquatic Chronic 3; H412 | 0.4089 |

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum

| | | |
|--|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 1/4/2018 |
| | | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid | | Version: 1.3 |
| 773636 | | |

occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|-------------------------------|--|-----------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | TWA | 5 mg/m3 Mist | OSHA Z-1 |
| | | TWA | 5 mg/m3 Inhalable fraction | ACGIH |
| | | TWA | 5 mg/m3 Mist | OSHA P0 |
| | | TWA | 5 mg/m3 Mist | NIOSH REL |
| | | ST | 10 mg/m3 Mist | NIOSH REL |
| MINERAL OIL | | PEL | 5 mg/m3 particulate | CAL PEL |
| | | TWA | 5 mg/m3 Mist | OSHA Z-1 |
| | | TWA | 5 mg/m3 Inhalable fraction | ACGIH |
| | | TWA | 5 mg/m3 Mist | OSHA P0 |
| | | TWA | 5 mg/m3 Mist | NIOSH REL |
| | | ST | 10 mg/m3 Mist | NIOSH REL |
| | | PEL | 5 mg/m3 particulate | CAL PEL |

Hazardous components without workplace control parameters

| Components | CAS-No. |
|--------------|---------|
| METHACRYLATE | |

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

| | |
|---------------------------------------|--|
| COPOLYMER | |
| ALKOXYLATED LONG-CHAIN ALKYL AMINE | |

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : red

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup

Evaporation rate : > 1
Ethyl Ether

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

| | |
|--|---|
| Flammability (solid, gas) | : No data available |
| Upper explosion limit | : 6 %(V) GLP: Calculated Explosive Limit |
| Lower explosion limit | : 1 %(V) GLP: Calculated Explosive Limit |
| Vapour pressure | : 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure |
| Relative vapour density | : No data available |
| Density | : 0.862 g/cm3 (15.56 °C) |
| Solubility(ies) | |
| Water solubility | : No data available |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : ca. 43 mm2/s (40 °C) |
| Oxidizing properties | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Conditions to avoid | : excessive heat |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | carbon dioxide and carbon monoxide Hydrocarbons |

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:**ALKOXYLATED LONG-CHAIN ALKYL AMINE:**

Acute oral toxicity :

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Components:**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation

MINERAL OIL:

Result: Slight, transient irritation

METHACRYLATE COPOLYMER:

Result: No skin irritation

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: Corrosive to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation

MINERAL OIL:


Result: Slight, transient irritation

METHACRYLATE COPOLYMER:

Result: Irritating to eyes.

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: Corrosive

| | | |
|---|--|---------------------------|
|  | | Page: 8 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 1/4/2018 |
| | | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid | | Version: 1.3 |
| 773636 | | |

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

MX_DG

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL MARITIME DANGEROUS GOODS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_INWT_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

TDG RAIL C

| |
|---------------------|
| Not dangerous goods |
| |

TDG ROAD C

| |
|---------------------|
| Not dangerous goods |
| |

U.S. DOT - INLAND WATERWAYS

| |
|---------------------|
| Not dangerous goods |
| |

CFR RAIL C

| |
|---------------------|
| Not dangerous goods |
| |

U.S. DOT - ROAD

| |
|---------------------|
| Not dangerous goods |
| |

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 1/4/2018

SDS Number: R0200299

Valvoline™ DEX/MERC Automatic Transmission Fluid

Version: 1.3

773636

- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 05/22/2017

| | | | | | | | |
|--|---|--------|---|--------------|---|-----------------|---|
| <p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div> | <p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: black; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: black; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #cccccc;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | 0 | FLAMMABILITY | 1 | PHYSICAL HAZARD | 0 |
| HEALTH | 0 | | | | | | |
| FLAMMABILITY | 1 | | | | | | |
| PHYSICAL HAZARD | 0 | | | | | | |

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H402 Harmful to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

| | | |
|---|--|---------------------------|
|  | | Page: 12 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 1/4/2018 |
| | | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid | | Version: 1.3 |
| 773636 | | |


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

| | | |
|--|--|---------------------------|
|  | | Page: 13 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 1/4/2018 |
| | | SDS Number: R0200299 |
| Valvoline™ DEX/MERC Automatic Transmission Fluid | | Version: 1.3 |
| 773636 | | |

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System